



# MT-72 Robotic Moving Target System

## **Key Features:**

- Turns 360° on its own radius f or lifelike maneuverability
- Optional track system for consistent operation
- Wireless Variable Speed Control
- Standard Effective Range: up to 1000 meters line of sight
- Full Running Man Speeds
- Multi-mission Off-road/rugged terrain operation
- Armored (standard)
- High ground clearance
- 3D Manikin Mike<sup>™</sup> target with stop/stop-drop hit sense mount

All-terrain mover. Designed to operate on improved, range sites. Specifically, Hogan's Alleys, UACs, MOUTs, combat villages, sniper training, improved pathways and roadways, and limited undulating terrain.

Easy battery replacement for extended run times.

Target mounts for military E, F, and IVAN, Manikin Mike 3D, steel reactive plates and standard law enforcement target backers.

Ruggedized, all weather, all-steel construction with all-steel gearing and field serviceable with "plug and play" components.

**ATS Targets** (Advanced Training Systems) 651.429.8091 | atstargets.com







## **MT-72 SERIES SPECIFICATIONS**

DIMENSIONS	
Base	30"x23"x10" (LxWxH)
WEIGHT	SU XZS XIU (LXVVXII)
Base Unit (Standard)	96 lbs.
Base Unit (Armored)	136 lbs.
Stop/Drop with Manikin	14 lbs.
Carry capacity (Standard)	150 lbs.
ENVIRONMENTAL	130 lbs.
Temperature	32°F to 140°F
Rain	Water resistant, but cannot be submerged
Battery BASE	water resistant, but cannot be submerged
Туре	Sealed lead acid Capacity
	(6) 12VDC / 9Ah
	Built into 1 battery pack with 6
	Batteries, wired for 24V
Run time (Standard)	3 hours (50% duty Cycle)
Run time (Armored)	1.6 hours (50% duty Cycle)
	1.6 flours (50% duty Cycle)
Charger	IC
Type Input Voltage/Current	120VAC / 240A
Output Voltage/Current	12VDC / 12A
Drivetrain	12VDC
Motors	4 – 24V 120W 270rpm IP44 Motors
Tires	4 – 10" x 3.5" Pneumatic
Speed	0 to 11.75 feet/second Variable
	Forward or Reverse, Skid Steering
Radio	Fol ward of neverse, skild steering
Short-range	
Distance	Maximum effective range 1000 m line of sight
Frequency Standard	2.4 GHz Spread Spectrum Futaba or FlySky
Long Range or GPS (Option)	2.4 GHZ Spread Spectrum Futaba of Frysky
Distance	600 m line of sight
Frequency	900 MHz spread-spectrum  FCCID MCQ-XB900HP
	FCCID MICQ-AB900HP
Frequency Option 1	2.4 GHz spread-spectrum
	FCCID MCQ-XBEE3
Frequency Option 2 (Japan)	2.4 GHz spread-spectrum
	Japan Approvals R210-119309
Transmit Power	4mW







Armor (Optional)	
Weight	100 lbs.
Material	0.25" AR500 Plate
Protection	Up to .308 incidental
Optional Mounts	
	Dual Stake Pockets (standard)
	PT-61 A or B
	Mannequin Mike™ Stop/Drop Reactive
	Mannequin Mike™ Non-Reactive
	E, F, IVAN
	Surveillance cameras
	Portable lighting systems
	Mobile phones (for hostage negotiations)
	Fire-back (Paintball)

#### WHAT'S IN THE BOX:

- MT-72 Moving Target
- Battery pack
- **Battery Charger**
- Antenna
- Hit Sensor

#### **KEY ACCESSORIES TO CONSIDER:**

- Other target mounts
- Tracker System
- Target Backers
- Stop/Drop Mount Kit (optional)
- Manikin Mike 3D target Kit

### **INPUTS/OUTPUTS**







