



## PTX-TAB Bluetooth Wireless Controller

### Key Features:

- Controls up to 200 targets simultaneously
- Lightweight
- Durable
- Rechargeable Lithium Battery
- Up to 2000 meters range (600 meters standard)
- Stores complete courses of fire locally
- USB connectivity for programming via Windows computer, laptop or tablet

PTX-TAB Bluetooth wireless is compatible with all PT and/or FLEXI Series target systems. Offering a 600 Meter Range, FOUR (4) function modes, one controller can operate up to 200 PT and/or FLEXI Series target units simultaneously. Easily download customized courses of fire ATS Targets' UTC range control software with USB connectivity. Features lighted display for low light and night operation.

## PTX-TAB SERIES SPECIFICATIONS

DIMENSIONS	
Size	4.5" x 3" x 1" (LxWxH)
WEIGHT	
(Std w/ 2 batteries)	0.2 lb
RADIO	
Maximum effective range	900 MHz, frequency hopping 600 meters guaranteed, 1000 meters typical
POWER	
Battery	Lithium with micro USB charge port
RADIO	
Maximum effective range	900 MHz, frequency hopping 600 meters guaranteed, 1000 meters typical
Long Range or GPS (Option)	
Distance	600 m line of sight
Frequency	900 MHz spread-spectrum FCCID MCQ-XB900HP
Frequency Option 1	2.4 GHz spread-spectrum FCCID MCQ-XBEE3
Frequency Option 2 (Japan)	2.4 GHz spread-spectrum Japan Approvals R210-119309
Transmit Power	4mW
	Fire-back (Paintball)
CONNECTIVITY	
Port	USB

### WHAT'S IN THE BOX:

- PTX-TAB Bluetooth device
- USB Cable
- Plastic Carry Case
- Antenna

### KEY ACCESSORIES TO CONSIDER:

- UTC Software
- PTX-600 Handheld wireless controller