



## PTX Handheld Wireless Controller

### Key Features:

- Controls up to 200 targets simultaneously
- Lightweight
- Durable
- Backlight for low light training
- Battery powered
- Up to 2000 meters range (600 meters standard)
- Stores up to 10 complete courses of fire locally
- USB connectivity for programming via Windows computer, laptop or tablet

PTX-600 wireless target controller. Handheld controller is compatible with all PT and/or FLEXI Series target systems. Offering a 600 Meter Range, FOUR (4) function modes, one controller can operate up to 200 PT and/or FLEXI Series target units simultaneously. Easily download customized courses of fire ATS Targets' UTC range control software with USB connectivity. Features lighted display for low light and night operation.

## PTX SERIES SPECIFICATIONS

DIMENSIONS	
Size	4.5" x 3" x 1" (LxWxH)
WEIGHT	
(Std w/ 2 batteries)	0.5 lb
RADIO	
Maximum effective range	900 MHz, frequency hopping 600 meters guaranteed, 1000 meters typical
POWER	
PTX-200 and PTX-600	2 - 9V Alkaline Batteries
PTX-2000	4 - AA Alkaline Batteries
Run Time	40 hrs at 50% Duty Cycle
RADIO	
Maximum effective range	900 MHz, frequency hopping 600 meters guaranteed, 1000 meters typical
Long Range or GPS (Option)	
Distance	600 m line of sight
Frequency	900 MHz spread-spectrum FCCID MCQ-XB900HP
Frequency Option 1	2.4 GHz spread-spectrum FCCID MCQ-XBEE3
Frequency Option 2 (Japan)	2.4 GHz spread-spectrum Japan Approvals R210-119309
Transmit Power	4mW
	Fire-back (Paintball)
CONNECTIVITY	
Port	USB

### WHAT'S IN THE BOX:

- PTX Handheld device
- USB Cable
- Plastic Carry Case
- 2 Batteries (Std) 4 AA Batteries (2000)

### KEY ACCESSORIES TO CONSIDER:

- UTC Software
- PTX-TAB Bluetooth module for use with Windows and Android devices

### INPUTS/OUTPUTS

